

SUPERCUT

ENGINEERING WORKS

An ISO/TS 16949:2009 Certified Company

STYLE RX WEIGHT AND DIMENSIONS CHART

Measurements in Inches

Ring	Pitch Diameter	OD	Width	Height	Weight lbs.
RX 20	2.687	3.000	0.344	0.75	0.53
RX 23	3.250	3.672	0.469	1.00	1.15
RX 24	3.750	4.172	0.469	1.00	1.33
RX 25	4.000	4.313	0.344	0.75	.80
RX 26	4.000	4.406	0.469	1.00	1.42
RX 27	4.250	4.656	0.469	1.00	1.50
RX 31	4.876	5.297	0.469	1.00	1.73
RX 35	5.375	5.797	0.469	1.00	1.91
RX 37	5.875	6.297	0.469	1.00	2.09
RX 39	6.375	6.797	0.469	1.00	2.27
RX 41	7.125	7.547	0.469	1.00	2.54
RX 44	7.652	8.047	0.469	1.00	2.72
RX 45	8.313	8.734	0.469	1.00	2.96
RX 46	8.313	8.750	0.531	1.13	3.66
RX 47	9.000	9.656	0.781	1.63	8.56
RX 49	10.63	11.047	0.469	1.00	3.79
RX 50	10.63	11.156	0.656	1.25	5.36
RX 53	12.75	13.172	0.469	1.00	4.56
RX 54	12.75	13.281	0.656	1.25	6.45
RX 57	15.00	15.422	0.469	1.00	5.36
RX 63	16.50	17.391	1.063	2.00	26.40
RX 65	18.50	18.922	0.469	1.00	6.63
RX 66	18.50	19.031	0.656	1.25	9.39
RX 69	21.00	21.422	0.469	1.00	7.52
RX 70	21.00	21.656	0.781	1.63	20.14
RX 73	23.00	23.467	0.531	1.25	11.63
RX 74	23.00	23.656	0.781	1.63	22.10
RX 82	2.250	2.672	0.469	1.00	0.79
RX 84	2.500	2.922	0.469	1.00	0.88
RX 85	3.125	3.547	0.531	1.00	0.88
RX 86	3.563	4.078	0.594	1.13	1.79
RX 87	3.938	4.453	0.594	1.13	1.98
RX 88	4.875	5.484	0.688	1.25	3.22
RX 89	4.500	5.109	0.719	1.25	2.98
RX 90	6.125	6.875	0.781	1.75	6.82
RX 91	10.25	11.29	1.187	1.78	17.10
RX 99	9.250	9.672	0.4689	1.00	3.31
RX 201	1.813	2.026	0.2260	0.44	0.14
RX 205	2.250	2.453	0.2189	0.44	0.16
RX210	3.500	3.844	0.3752	0.75	0.77
RX 215	5.125	5.545	0.4689	1.00	1.76