

SUPERCUT

ENGINEERING WORKS

An ISO/TS 16949:2009 Certified Company

STYLE BX SELECTION CHART

Nominal Flange Bore (in.)

Ring	2000 psi	3000 psi	5000 psi	10000psi	15000psi	20000psi	Gasket Weight lbs.
BX-150				1 ¹¹ / ₁₆	1 ¹¹ / ₁₆		0.29
BX-151				1 ¹³ / ₁₆	1 ¹³ / ₁₆	1 ¹³ / ₁₆	0.33
BX-152				2 ¹ / ₁₆	2 ¹ / ₁₆	2 ¹ / ₁₆	0.42
BX-153				2 ⁹ / ₁₆	2 ⁹ / ₁₆	2 ⁹ / ₁₆	0.63
BX-154				3 ¹ / ₁₆	3 ¹ / ₁₆	3 ¹ / ₁₆	0.87
BX-155				4 ¹ / ₁₆	4 ¹ / ₁₆	4 ¹ / ₁₆	1.22
BX-156				7 ¹ / ₁₆	7 ¹ / ₁₆	7 ¹ / ₁₆	4.14
BX-157				9	9		6.55
BX-158				11	11		9.60
BX-159				13 ⁵ / ₈			14.41
BX-160			13 ⁵ / ₈				6.75
BX-161			16 ³ / ₄				11.26
BX-162			16 ³ / ₄	16 ³ / ₄			4.95
BX-163			18 ³ / ₄				14.68
BX-164				18 ³ / ₄			21.55
BX-165			21 ¹ / ₄				18.71
BX-166				21 ¹ / ₄			27.11
BX-167	26 ³ / ₄						17.82
BX-168		26 ³ / ₄					22.19
BX-169				5 ¹ / ₈			1.74
BX-170				6 ⁵ / ₈	6 ⁵ / ₈		2.19
BX-171				8 ⁹ / ₁₆	8 ⁹ / ₁₆		2.72
BX-172				11 ⁵ / ₃₂	11 ⁵ / ₃₂		3.42